

# SPEAKMAN®

## SEF-9000

### EYESAVER® FAUCET SPECIFICATIONS

#### DESCRIPTION

The SEF-9000 Eyewash system is a combination Speakman eyewash/drench hose and a SC-5811 service sink faucet. This creative design allows the eyewash to be attached directly to the faucet's cold water integral stop port and permits both units to be operated independently. As a result only one plumbing connection is required and with the built-in check valve there is never a worry about delivering scalding water to the eyes.

#### SPECIFICATIONS

##### EYEWASH

**Supply:** Speakman SC-5811-RCP service sink faucet's cold water integral stop port

**Activator:** Squeeze valve with automatic stay open device

**Spray Heads:** (2) yellow ABS plastic spray outlets with flip-top dust caps

**Performance:** 2.4 gpm @ 30 psi

**Backflow Prevention:** Integral vacuum breaker and check valve

**Compliance:** ANSI Z358.1

##### SERVICE SINK FAUCET

**Supply:** ½" NPT female inlets

**Activator:** Vandal resistant four arm handles with color coded indexes

**Cartridges:** Perfect® valves with ¼ turn ceramic cartridges covered by a 25-year warranty

**Outlet:** Cast brass nozzle with ¾" hose thread, pail hook and top brace

**Performance:** 4 gpm (min) @ 20 psi


**Backflow Prevention:** Integral vacuum breaker

**Compliance:** ASME A112.18.1-2000 & CSA B125-98

**Universal Emergency Sign Included**

#### OPTIONS

- TW Addition of SE-370 thermostatic mixing valve
- FM Eyewash permanently fastened to wall, eliminating back flow prevention requirement



Job Name _____
Location _____
Architect/Engineer _____
Sales Representative _____
Wholesaler _____
Date _____ Model # _____