

## ANYSTREAM®

**S-2558**



**S-2559**



**S-2658**



**S-2659**



**S-2252-E20**



**S-2253-E20**  
**S-2253-E175**  
**S-2253-E15**



**S-2005-H-E2**



**S-2005-HB-E2**



## Downpour Showerheads

### GENERAL SPECIFICATION

#### ANYSTREAM RAIN™

Polished chrome plated 8" diameter solid brass downpour showerhead. 96 spray streams positioned for a full-body coverage rain shower. Brass ball swivel joint connection. Flow control device reduces flow to 2.5 gpm/9.46 lpm maximum to meet existing ANSI A112.18.1 standard. 1/2" NPT inlet.

**S-2558**

Anystream Rain™ downpour shower with patented brass lever flow control.

**S-2559**

Anystream Rain™ downpour showerhead only.

**S-2658**

Anystream Rain™ downpour shower with patented brass lever flow control. With "S" shaped shower arm.

**S-2659**

Anystream Rain™ downpour rain showerhead. With "S" shaped shower arm.

#### OPTIONS (S-2558, S-2559, S-2658, S-2659)

SUFFIX	DESCRIPTION
<input type="checkbox"/> BN	Brushed nickel finish
<input type="checkbox"/> ORB	Oil rubbed bronze finish
<input type="checkbox"/> PB	Polished brass finish

### GENERAL SPECIFICATION

#### LOW FLOW SHOWERHEAD

Full-body, infinitely adjustable spray streams. Anystream plunger nozzle system delivers great spray intensity at any water pressure. Large operating handle for precise control and easy spray selection. Meets ANSI A112.18.1. 1/2" NPT inlet. Recommended for U.S. Green Building Council LEED Rating System Project Certification.

**S-2252-E20**

6-jet showerhead. 48 sprays. 2-3/4" face diameter. Solid brass large-body construction. Pressure-compensating Autoflo device limits flow to 2.0 gpm/7.6 lpm

**S-2253-E20**

4-jet showerhead. 32 sprays. 2-1/4" face diameter. Pressure-compensating Autoflo device limits flow to 2.0 gpm/7.6 lpm.

**S-2253-E175**

4-jet showerhead. 32 sprays. 2-1/4" face diameter. Pressure-compensating Autoflo device limits flow to 1.75 gpm/6.6 lpm

**S-2253-E15**

4-jet showerhead. 32 sprays. 2-1/4" face diameter. Pressure-compensating Autoflo device limits flow to 1.5 gpm/5.6 lpm

**S-2005-H-E2**

5-jet showerhead. 40 sprays. 3-1/4" face. Adjustable spray with massage. Pressure-compensating Autoflo device limits flow to 2.0 gpm/7.6 lpm.

**S-2005-HB-E2**

5-jet showerhead. 40 sprays. 4-1/4" face. Adjustable spray with massage. Pressure-compensating Autoflo device limits flow to 2.0 gpm/7.6 lpm.

This space for Architect/Engineer approval.

